



FLEXY POS

CONFIGURATION FLEXIBILITY

APPEALING DESIGN

FANLESS SOLUTION



PSM
TECH

www.psm-tech.com



FEATURES

Processor	Intel® Celeron® N3350 Dual Core @1.1GHz (burst 2.4GHz), 2MB L2 Cache, 6W TDP
Memory	Quad Channel soldered down LPDDR4 memory, up to 8GB
Graphics	Integrated Intel® HD Graphics 505 or 500 series controller, with up to 18 Execution Units 4K HW decoding and encoding of HEVC(H.265), H.264, VP8, SVC, MVC
Display	13.3" 1920x1080 TFT LCD display with touch screen
Video	Two multimode Display Port on miniDP++ connectors
Mass Storage	Up to 64GB eMMC drive onboard Optional SATA M.2 SSD module up to 512GB
Networking	2 x Gigabit Ethernet ports Optional M.2 4G LTE module (alternative to M.2 SSD), with internal microSIM slot Optional M.2 WiFi/BT LE module
USB	2 x USB 3.0 Type-A sockets on Front Panel
Audio	Internal HD Audio codec Cirrus Logic CS4207 2 x integrated speaker 8Ω / 1W
Power Supply	DC Power jack with cable restraint 19VDC 40W
Security	Unique electronic serial number TPM security device Hardware protected chain of trust
Operating Temperature	0°C ÷ +60°C (Commercial version) Environment temperature measured near the heatsink's fins. Upon customer to verify that the temperature remains within the admissible range.
Dimensions	333 x 219 x 68 mm (main device only)
Accessories	Smart Card Reader (optional) Bar Code Reader (optional) Table/Wall/Ceiling VESA Stand (optional) Custom Accessories available on request